



Category		Spec				Remarks
Connector	NO:01	SC/APC SM/SX Green				
	NO:02					
Cable	NO:03	Fiber Type	G657A1	Diameter	Φ3.0mm	
		Material	PVC	Color	yellow	

Material no.	Length(M)	QTY	Reference Pictures	
			WQ-SA01-10HBY	1.5 ±0.03

performance	Endface	A class see table 01	3D	Radius of Curvature (mm)	7 ~ 25	100%
	IL	< 0.3 dB		Apex Offset(um)	< 50	95%
	RL	≥ 50 dB		Fiber High(nm)	±50	90%
	Working Temperature	-40 ℃ to +85 ℃				
	Storage Temperature	-40 ℃ to +85 ℃				
	Humidity	can work under 95% relative humidity environment normally				

Area	Class A standard (excellent)			Class B standard (Good)			Class C standard(Qualified)		
	Scratch	Dirty spots	Crack	Scratch	Dirty spots	Crack	Scratch	Dirty spots	Crack
① area:	NO	NO	NO	NO	NO	NO	NO	NO	NO
② area:	NO	NO	NO	NO	NO	NO	NO	NO	NO
③ area:	NO	NO	NO	1um 1pc allowed	1um 1pc allowed	1um 1pc allowed	1um 1pc allowed	1um 2pcs allowed	1um 2pcs allowed
④ area:	NO	NO	NO	1um 1pc allowed	1um 1pc allowed	1um 1pc allowed	1um 1pc allowed	1um 2pcs allowed	1um 2pcs allowed

The following tests must meet this result

Loss should be within the following limits in reference to the initial value

The difference between Initial Value and final test value should be ≤0.30 dB, Return loss should be ≥50 dB

Insert/Pull Test	<ul style="list-style-type: none"> ◆ Number of Pull/Insert: 500 times ◆ Record a data every 10 times ◆ Data is recorded 50 times in total ◆ Clean pins and adapter's elastic sleeve before recording very time, ∪ Not mechanical damage, such as deformation, loss, corrosion, relaxation and other phenomena 	Mechanical Performance
------------------	---	------------------------

Tensile Requirements	<ul style="list-style-type: none"> ◆ Load:50N ◆ Tensile variation in process of testing: 1N/S ◆ Duration:60s ◆ Tensile Point:0.22-0.28m distance from fiber cable ends 	Mechanical Performance
----------------------	--	------------------------

Torsion Requirements	<ul style="list-style-type: none"> ∪ Applied force: 4 N ◆ The distance between the Torsion point and Connector is 0.2cm ◆ Max Torsion Angle: $\pm 180^\circ$ ◆ Number of torsions:25 times 	Mechanical Performance
----------------------	---	------------------------

High and Low Temperature Test Requirements	<ul style="list-style-type: none"> ◆ High Temperature=$+75^\circ\text{C}$, Temperature rate of change: $1^\circ\text{C} / \text{min}$ ◆ Low Temperature=-25°C, Temperature rate of change $1^\circ\text{C} / \text{min}$ ◆ High and low temperature points to stay four hours separately ◆ Duration: 96h ◆ Cycles: 12 times ◆ Keep 2 hours at 25°C, then test ◆ Insertion value should be tested at least one time per 10 mins. in process of testing. 	Mechanical Performance
--	--	------------------------

Low Temperature Requirements	<ul style="list-style-type: none"> ◆ Temperature=$-25^\circ\text{C} \pm 2^\circ\text{C}$ ◆ Duration:96H ◆ 2 hours returned to 25°C ◆ Test after Keeping 2 hours at 25°C ◆ Insertion value should be tested at least one time per 60 mins. in process of testing. 	Mechanical Performance
------------------------------	--	------------------------

High Temperature Requirements	<ul style="list-style-type: none"> ◆ Temperature=$+75^{\circ}\text{C} \pm 2^{\circ}\text{C}$ ◆ Duration:96H ◆ 2 hours returned to 25°C ◆ Test after Keeping 2 hours at 25°C ◆ Insertion value should be tested at least one time per 60 mins. in process of testing. 	Mechanical Performance
-------------------------------	--	------------------------

Humidity Requirements	<ul style="list-style-type: none"> ◆ Temperature=$+40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ ◆ humidity =$93\% \pm 5\%RH$ ◆ Duration:96H ◆ Test after Keeping 2 hours at 25°C ◆ Insertion value should be tested at least one time per 60 mins. in process of testing. 	Mechanical Performance
-----------------------	--	------------------------

Water Immersion Requirements	<ul style="list-style-type: none"> ◆ elevation of water:150mm ◆ Temperature:room temperature/running water ◆ Soaking time:168 h ◆ Insertion value should be tested at least one time per 10 mins. in process of testing. 	Mechanical Performance
------------------------------	--	------------------------