

# Fiber Optic Distribution Box 8 ports FQX-08-03+PW08

### Description

HBY Model No. FQX-08-03+PW08, this distribution box can realize the functions of fiber fusion, distribution and scheduling in the FTTH system. This fiber box made of new ABS material, and its shell is strong and durable. And IP65's protection rating allows it to be installed and used outdoors. Internally







#### **Feature**

- 1. The body is made of high quality engineering plastic with good strength;
- 2. With safe special-shaped lock, the box can be opened easily and has good water-proof performance, suitable for indoor and outdoor natural environments .
- 3. With the independent rubber sealing plug for drop cable, better waterproof performance;
- 4. With double-page design, the box can be installed and maintained easily, the fusion and termination are completely separated; 5. The drop leaf can be installed 1 pcs of 1\*8 tube splitter

#### **Ordering Information**

| FiberNex PN    | Capacity<br>(single<br>core) | Adaptor<br>type |  | Description                                    |
|----------------|------------------------------|-----------------|--|--|
| FQX-08-03+PW08 | 8 Port                       | SC              |  | Fiber Optic Subscriber Distribution box 8 Port |
|                |                              |                 |  | SC type  |

\*Does not including adaptors, pigtails and splitter.Additional configurations can be made if required



## **Product Specifications**

| Item                      | Fiber Optic Distribution Box8 ports |
|---------------------------|-------------------------------------|
| Dimension (mm)            | 340MM*210MM*103MM                   |
| Material                  | ABS                                 |
| Weight (Kg)               | 2kg                                 |
| No. of Cable Inlet/Outlet | 2IN-8OUT                            |
| Type of inlet             | Waterproof connectors               |
| Adaptor accommodating     | Max.8 port of SC, FC, LC, E2K       |
| Splitter                  | One for 1x8 splitter; r             |
| Working Temperature       | -30deg.C~80deg.C                    |
| Protection Grade          | IP65                                |

## Packing Info

• Carton packing: 10sets/carton

• Carton size: 47.5\*37\*59cm

• Weight: 21kg/carton

- www.hbyweb.ru
- www.hbyweb.com.br
- E-mail:sales@hbyweb.com